



1997-13 ALIGNMENT SPECIFICATIONS

Street Specs

FRONT

Rake 20mm Positive
 Toe .070° Total Toe In
 Camber 0-.250° Negative
 Caster 7.00-8.5° Positive

REAR

Toe .270° Total Toe In
 Camber .25° Negative

Track Specs

FRONT

Rake 0 to 10mm Positive
 Toe 0 - .070° Total Toe Out
 Camber 1.5 – 2.5° Negative
 Caster 6.3-7.5° Positive

REAR

Toe .270 to .675° Total Toe In
 Camber .500 – 1.00° Negative

Advanced Street Specs

FRONT

Rake 10mm Positive
 Toe 0 - Total
 Camber .50-1.25° Negative
 Caster 6.25-8° Positive

REAR

Toe .270° Total Toe In
 Camber .25 – .5° Negative

Drag Race

FRONT

Rake 10mm Negative
 Toe 0 Total
 Camber 0 to .2° Positive
 Caster 7.5-8.5° Positive

REAR

Toe .021-.064° Total Toe In
 Camber 0 to .10° Negative

**All measurements based on stock tire sizes:
 Front: 25.7" | Rear: 26.5"**

These specifications are starting point for base line packages. Rubber bushings can effect final numbers. For pure track time cars please call for specific settings.